

Under Shanshan Group, Top500 Enterprise in China, Ulica Solar produces our own high quality solar cells and modules starting from August 2005. Our product range covers all from off-grid panels to on-grid panels, both mono-crystalline and poly-crystalline, suitable for all types of installation from residential to commercial projects.

MONO 72CELL PERC



Higher Conversion Efficiency

With new generation of PERC technology, the average conversion efficiency of the cells could reach 21.9%



Positive power output (0~+5W)



Outstanding mechanical load resistance

Snow load 5400Pa (Frontside), and Wind load 3800Pa (Backside)



High performance under low light conditions

Cloudy days, Rainy days



Anti-PID (potential induced degradation) Test

Passed anti-PID test under Damp Heat 85°C and 85% RH 96Hours



Durability against extreme environmental conditions

Salt mist corrosion test, Ammonia corrosion test, Dust & Sand test, Fire test, certified by TÜV SÜD





Double EL test before and after lamination

Highly control the micro cracks and invisible defects.



World famous insurance

CHUBB(USA), Solar Insurance&Finance(Netherlands)



12-year product warranty

25-year linear power warranty



MONO 370W/375W/380W/385W



ELECTRICAL PERFORMANCE

Electrical Parameters Standard Test Conditions

Module Type			UL-370M-72	UL-375M-72	UL-380M-72	UL-385M-72
Power Output	P _{max}	W	370	375	380	385
Power Tolerance	ΔP _{max}	W	0/+5W			
Module Efficiency	η _m	%	19.07	19.33	19.58	19.84
Voltage at P _{max}	V _m	V	39.4	39.5	39.6	39.7
Current at P _{max}	I _m	A	9.39	9.49	9.60	9.70
Open-Circuit Voltage	V _{oc}	V	48.2	48.4	48.5	48.6
Short-Circuit Current	I _{sc}	A	9.88	9.96	10.07	10.17

STC: 1000W/m² irradiance, 25°C module temperature, AM1.

THERMAL CHARACTERISTICS

Nominal Operating Cell Temperature	NOCT	°C	45±2
Temperature Coefficient of P _{max}	γ	%/°C	-0.390
Temperature Coefficient of V _{oc}	β _{voc}	%/°C	-0.290
Temperature Coefficient of I _{sc}	α _{isc}	%/°C	+0.049

OPERATING CONDITIONS

Max. System Voltage	1000V/1500V
Max. Series Fuse Rating	15A
Operating Temperature Range	-40°C~85°C
Max static snow load	5400Pa
Max static wind load	3800Pa
Application Class	A

CONSTRUCTION MATERIALS

Front Cover(material/type/thickness)	low-iron tempered glass/3.2mm
Cell(quantity/material/type/dimension)	72/monocrystalline/156.75x156.75mm
Encapsulant(material)	ethylene vinyl acetate(EVA)
Frame(material/anodization color)	anodized aluminum alloy/silver or black
Junction Box(protection degree)	IP67
Cable(length/cross-sectional area)	1100mm/4mm ²
Plug Connector	MC4 compatible

GENERAL CHARACTERISTICS

Dimension(L/W/H)	1956/992/40mm
Weight	21.5kg

PACKING CONFIGURATION


Pallet Size(L/W/H)	1990/1120/2460mm
Pallet Weight	1357kg
Pieces per Pallet	56pcs
Pieces per Container	672pcs

INTERNATIONAL CERTIFICATES



- TÜV SÜD, TÜV NORD, UL, CE, JET, CEC, MCS, CQC, INMETRO, NRE, KS
- ISO9001:2015
- ISO14001:2015
- BS OHSAS 18001:2007

I-V CURVE

I-V characteristics at different irradiances



I-V characteristics at different temperature



Please read the instruction manual in this entirety before handing, installing, and operating Ulica Solar modules.

Due to continuous innovation, research and improvement, the specification is subject to change without prior notice.